



AUGERS

PA15 | PA30 | CA15 | CA25



WORKSITE PRO™

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

PA15 / PA30 / CA15 / CA25

- Choice of heavy-duty PA15 and PA30 and lighter-duty CA15 and CA25 means there's a Worksite Pro auger perfect for any task.
- Worksite Pro augers feature self-plumbing auger bits, and reverse rotation allows quick withdrawal when obstructions are encountered.
- Planetary auger's in-line drive design eliminates the need for complicated chain-and-sprocket reduction.
- Chain auger's fixed-chain center eliminates the need for adjustments, and floating drive sprocket ensures constant chain alignment.
- Heavy-duty gear design of planetary auger ensures long life with normal maintenance and service. Completely sealed drive unit eliminates the need for costly plumbing repair and maintenance. Chain auger's spring-loaded, double-lipped seals guard against contamination.
- Like all Worksite Pro attachments, these augers are optimized to work with John Deere Skid Steers, Compact Track Loaders, Compact Excavators, Compact 4WD Loaders, and 110 Tractor Loader Backhoe. In addition, they are compatible with most competitive models of skid steers. See your local John Deere dealer for details.

	PA15	PA30	CA15	CA25
Maximum auger bit diameter	24 in. (610 mm)	36 in. (914 mm)	18 in. (457 mm)	36 in. (914 mm)
Overall auger bit length	48 in. (1219 mm)	48 in. (1219 mm)	48 in. (1219 mm)	48 in. (1219 mm)
Minimum hydraulic flow	6 gpm (23 L/min.)	14 gpm (53 L/min.)	6 gpm (23 L/min.)	14 gpm (53 L/min.)
Maximum hydraulic flow	15 gpm (57 L/min.)	30 gpm (114 L/min.)	15 gpm (57 L/min.)	30 gpm (114 L/min.)
Maximum continuous operating psi	3,100 psi (20 684 kPa)	3,100 psi (20 684 kPa)	3,100 psi (20 684 kPa)	3,100 psi (20 684 kPa)
Output shaft options	2-in. (51 mm) Hex.	2-in. (51 mm) Hex.	2-in. (51 mm) Hex.	2-in. (51 mm) Hex
Output torque	1,433 lb.-ft. (1942 Nm)	2,791 lb.-ft. (3784 Nm)	1,460 lb.-ft. (1979 Nm)	2,843 lb.-ft. (3855 Nm)
Output speed:				
6 gpm (23 L/min.)	38 rpm		38 rpm	
8 gpm (30 L/min.)	51 rpm		50 rpm	
10 gpm (38 L/min.)	64 rpm		63 rpm	
12 gpm (45 L/min.)	77 rpm		75 rpm	
15 gpm (57 L/min.)	96 rpm	49 rpm	94 rpm	48 rpm
18 gpm (68 L/min.)		59 rpm		58 rpm
20 gpm (76 L/min.)		66 rpm		65 rpm
28 gpm (106 L/min.)		92 rpm		91 rpm
Vehicle compatibility	17ZTs, 27D	317, 320, 325, 328, 332, CT322, CT332, 35D, 50D, 110 TLB, 244J	17ZTs, 27D	317, 320, 325, 328, 332, CT322, CT332, 35D, 110 TLB, 244J

WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

