



JOHN DEERE



BACKHOES

BH8 | BH9 | BH11



WORKSITE PRO

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

BH8 / BH9 / BH11

- Powerful Worksite Pro™ Backhoes offer a combination of productivity, ease of operation, and unmatched durability.
- One-hundred-eighty-degree swing allows maximum efficiency in confined areas.
- For extreme digging conditions, heavy-duty buckets are available with tapered sides for greater dump-and-fill performance, and large teeth and tooth shanks add durability.
- Optional quick-coupler also utilized on Deere 27 and 35 Series Compact Excavators.
- Low-profile console offers excellent visibility.
- The operator's station is easy to enter and exit, thanks to a convenient grab rail and open design. Its seat with fore-and-aft adjustment and large footrests with non-slip surfaces also ensure comfortable operation for extended periods.
- All Worksite Pro Backhoes are equipped with a connect-under-pressure male coupler.
- Metered hydraulic spools and centralized two-lever control of boom lift, swing, dipperstick, and bucket allow precise control of backhoe movement.
- Single lever locks the boom in place for secure transport. Can be engaged or disengaged from the seat.
- Worksite Pro Backhoes are optimized to work with John Deere skid steers and compact track loaders. They're backed by a one-year warranty and one-of-a-kind parts and service. See your local John Deere skid steer dealer for details.

	BH8	BH9	BH11
Transport height	90 in. (2286 mm)	94 in. (2388 mm)	115 in. (2921 mm)
Overall transport length			
240, 250, 317, 320, and CT322	179 in. (4547 mm)	184 in. (4674 mm)	189 in. (4801 mm)
260, 270, 280, 325, 328, 332, and CT332	193 in. (4902 mm)	198 in. (5029 mm)	203 in. (5156 mm)
Digging depth: Maximum	107 in. (2718 mm)	117 in. (2972 mm)	134 in. (3404 mm)
2-ft. (0.6 m) flat bottom	105 in. (2667 mm)	115 in. (2921 mm)	132 in. (3353 mm)
8-ft. (2.4 m) flat bottom	84 in. (2134 mm)	98 in. (2489 mm)	115 in. (2921 mm)
Straight wall	60 in. (1524 mm)	68 in. (1727 mm)	92 in. (2337 mm)
Reach from swing pivot	142 in. (3607 mm)	155 in. (3937 mm)	173 in. (4394 mm)
Loading height	88 in. (2235 mm)	95 in. (2413 mm)	107 in. (2718 mm)
Loading reach	46 in. (1168 mm)	61 in. (1549 mm)	68 in. (1727 mm)
Stabilizer spread: Transport	54 in. (1372 mm)	64 in. (1626 mm)	64 in. (1626 mm)
Operating	99 in. (2515 mm)	116 in. (2946 mm)	116 in. (2946 mm)
Bucket rotation	180 degrees	180 degrees	180 degrees
Swing arc	180 degrees	180 degrees	180 degrees
Attachment weight (with 18-in. [457 mm] bucket)	1,610 lb. (732 kg)	1,796 lb. (816 kg)	2,061 lb. (937 kg)
Craning capacity	820 lb. (372 kg)	905 lb. (410 kg)	985 lb. (447 kg)
Digging force: Using bucket cylinder	3,730 lb. (1692 kg)	6,000 lb. (2721 kg)	6,200 lb. (2812 kg)
Using dipperstick cylinder	2,435 lb. (1104 kg)	3,250 lb. (1474 kg)	4,000 lb. (1814 kg)
Backhoe system relief setting	2,425 psi (16 720 kPa)	2,425 psi (16 720 kPa)	2,425 psi (16 720 kPa)

BH8, BH9, AND BH11 BUCKETS AND CAPACITIES

Pin-on buckets: 14-in. (356 mm) heavy-duty	1.74 cu. ft. (0.049 m³)	1.14 cu. ft. (0.032 m³)	106 lb. (48 kg)
18-in. (457 mm) heavy-duty	2.68 cu. ft. (0.076 m³)	1.76 cu. ft. (0.050 m³)	126 lb. (57 kg)
24-in. (610 mm) heavy-duty	3.71 cu. ft. (0.105 m³)	2.42 cu. ft. (0.069 m³)	146 lb. (66 kg)
36-in. (914 mm) heavy-duty	5.76 cu. ft. (0.163 m³)	3.77 cu. ft. (0.107 m³)	195 lb. (88 kg)
Quick-coupler buckets: 12-in. (305 mm) heavy-duty	1.33 cu. ft. (0.038 m³)	1.09 cu. ft. (0.031 m³)	124 lb. (56 kg)
18-in. (457 mm) heavy-duty	2.33 cu. ft. (0.066 m³)	1.76 cu. ft. (0.050 m³)	152 lb. (69 kg)
24-in. (610 mm) heavy-duty	3.29 cu. ft. (0.093 m³)	2.42 cu. ft. (0.069 m³)	175 lb. (80 kg)

WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

