



JOHN DEERE



# COLD PLANERS

CP12C | CP18C | CP24C | CP30C



**WORKSITE PRO™**

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

# CP12C / CP18C / CP24C / CP30C

- Ideal for milling asphalt and concrete surfaces damaged from cracks, frost heaves, and potholes.
- Standard-flow model CP12C produces high torque for professional operation. High-flow hydraulic models (CP18C, CP24C, and CP30C) offer increased cold-planing production.
- Standard-flow model (CP12C) equipped with manual side shift, tilt, and depth control for planer positioning.
- High-flow models offer fingertip, electrical control of tilt, depth, and side shift for exact and easy cold-planer positioning.
- Planetary drum drive adds service life. Hinged access cover permits easy cold-planer pick maintenance.
- Worksite Pro™ cold planers are optimized to work with John Deere 300-Series Skid Steers. Plus, they're backed by a one-year warranty and one-of-a-kind parts and service. See your local John Deere Skid Steer CWP dealer for details.

	CP12C	CP18C	CP24C	CP30C
<b>Compatibility</b> . . . . .	317, 320, 325, 328, and CT322	320, 325, 328, 332, CT322, and CT332	325, 328, 332, and CT332	325, 328, 332, and CT332
<b>Hydraulic flow required</b> . . . . .	15–22 gpm (56–83 L/min.)	29–41 gpm (109–155 L/min.)	29–41 gpm (109–155 L/min.)	29–41 gpm (109–155 L/min.)
<b>Hydraulic pressure required</b> . . . . .	2,500–3,000 psi (17 240–20 685 kPa)	2,500–3,500 psi (17 240–24 130 kPa)	2,500–3,500 psi (17 240–24 130 kPa)	2,500–3,500 psi (17 240–24 130 kPa)
<b>Hydraulic horsepower required</b> . . . . .	22–39 hp (16.4–29.1 kW)	42–72 hp (31.6–53.4 kW)	42–72 hp (31.6–53.4 kW)	42–72 hp (31.6–53.4 kW)
<b>Planing width</b> . . . . .	12 in. (305 mm)	18 in. (457 mm)	24 in. (610 mm)	30 in. (762 mm)
<b>Planing depth</b> . . . . .	0–5 in. (0–127 mm)	0–5 in. (0–127 mm)	0–5 in. (0–127 mm)	0–5 in. (0–127 mm)
<b>Tilt capability</b> . . . . .	±11 deg.	±8 deg.	±8 deg.	±8 deg.
<b>Side-shift capability</b> . . . . .	0–19 in. (0–483 mm)	–3–22 in. (–76–559 mm)	–3–22 in. (–76–559 mm)	–3–22 in. (–76–559 mm)
<b>Number of carbide teeth</b> . . . . .	37	45	57	69
<b>Operating weight</b> . . . . .	1,500 lb. (680 kg)	2,200 lb. (998 kg)	2,400 lb. (1090 kg)	2,600 lb. (1180 kg)

www.JohnDeere.com

## WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

