



JOHN DEERE



MULTI-PURPOSE BUCKETS

MP66 | MP72 | MP78 | MP84



WORKSITE PRO

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

MP66 / MP72 / MP78 / MP84

- Capable of bulldozing, scraping, loading, metering, and clamping material, a Worksite Pro™ Multi-Purpose Bucket is ideal for many applications.
- Low-profile geometry allows superior visibility to the cutting edge, increasing efficiency.
- Rugged torque-tube design equalizes load forces when clamping.
- Heavy-duty design includes tough high-carbon cutting edges, wear-resistant 1055 high-carbon steel at key wear points, and precision cylinders with easy-to-service hardened rods. All pivot points are lubricated with grease fittings.
- To further increase durability and performance, buckets are predrilled for optional bolt-on, replaceable cutting edges or toothbars.
- Like all Worksite Pro attachments, these multi-purpose buckets are optimized to work with John Deere 200 and 300 Series Skid Steers, and are compatible with most competitive models. See your local John Deere skid steer dealer for details.

	MP66	MP72	MP78	MP84
Overall Width	66.75 in. (1695 mm)	72.75 in. (1848 mm)	78.75 in. (1981 mm)	84.75 in. (2153 mm)
Overall Height	28 in. (711 mm)	28 in. (711 mm)	28 in. (711 mm)	28 in. (711 mm)
Overall Depth	36 in. (914 mm)	36 in. (914 mm)	36 in. (914 mm)	36 in. (914 mm)
Heaped Bucket Capacity	12 cu. ft. (0.34 m ³)	13.1 cu. ft. (0.38 m ³)	14.2 cu. ft. (0.40 m ³)	15.4 cu. ft. (0.43 m ³)
Struck Bucket Capacity	8.6 cu. ft. (0.24 m ³)	9.4 cu. ft. (0.27 m ³)	10.0 cu. ft. (0.28 m ³)	10.5 cu. ft. (0.29 m ³)
Empty Weight	866 lb. (394 kg)	918 lb. (417 kg)	998 lb. (452 kg)	1,030 lb. (468 kg)
Cutting Edge Dimensions (1055 high-carbon steel):				
Front Half (front)	0.75 x 6 in. (19 x 152 mm)	0.75 x 6 in. (19 x 152 mm)	0.75 x 6 in. (19 x 152 mm)	0.75 x 6 in. (19 x 152 mm)
Front Half (rear)	0.75 x 4 in. (19 x 102 mm)	0.75 x 4 in. (19 x 102 mm)	0.75 x 6 in. (19 x 152 mm)	0.75 x 6 in. (19 x 152 mm)
Rear Half	0.50 x 6 in. (12.7 x 152 mm)	0.50 x 6 in. (12.7 x 152 mm)	0.50 x 6 in. (12.7 x 152 mm)	0.50 x 6 in. (12.7 x 152 mm)
Cylinders				
Bore	2.75 in. (70 mm)	2.75 in. (70 mm)	2.75 in. (70 mm)	2.75 in. (70 mm)
Stroke	6 in. (152 mm)	6 in. (152 mm)	6 in. (152 mm)	6 in. (152 mm)
Rod Diameter	1.5 in. (38 mm)	1.5 in. (38 mm)	1.5 in. (38 mm)	1.5 in. (38 mm)
Skid Steer Compatibility	240, 250, 317, 320	240, 250, 260, 270, 317, 320, 325, 328	260, 270, 280, 325, 328, 332	260, 270, 280, 325, 328, 332
John Deere Standard Warranty	One-year unlimited hours	One-year unlimited hours	One-year unlimited hours	One-year unlimited hours

www.JohnDeere.com



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

