



JOHN DEERE



# PICK-UP BROOMS

BR60 | BP72 | BR72  
BP84 | BR84



**WORKSITE PRO™**

SPECIFICATIONS

# BR60 / BP72 / BR72 / BP84 / BR84

- Brooms feature a 25-inch-diameter brush with 50/50 poly wire brush segments and a baffle to hold debris in bucket.
- Heavy-duty, high-torque drive motor is coupled to the brush core through a 1-inch splined shaft.
- Bolt adjustment on brush provides infinite height control.
- Two standard caster wheels (not on fixed brooms) allow for better balance and stability when sweeping.
- During bristle replacement, the drive motor can be pulled from the brush core without disconnecting any hydraulic lines. This means less mess, less cleanup, and little chance of hydraulic fluid contamination.
- Optional gutter brush has adjustable flow to allow for different material applications or ability to turn off when not in use.
- Like all Worksite Pro™ attachments, these pick-up brooms are optimized to work with John Deere 300-Series Skid Steers and Compact Track Loaders, 244J Loader, and 110TLB. They're compatible with many competitive models, too. See your local John Deere skid steer dealer for details.

	BR60	BP72	BR72	BP84	BR84
<b>Brush Diameter</b> . . . . .	25 in. (635 mm)	25 in. (635 mm)	25 in. (635 mm)	25 in. (635 mm)	25 in. (635 mm)
<b>Core Diameter</b> . . . . .	6.38 in. (162 mm)	6.38 in. (162 mm)	6.38 in. (162 mm)	6.38 in. (162 mm)	6.38 in. (162 mm)
<b>Number of Wafers</b> . . . . .	34	44	44	50	50
<b>Sweeping Width</b> . . . . .	60 in. (1524 mm)	72 in. (1828 mm)	72 in. (1828 mm)	84 in. (2133 mm)	84 in. (2133 mm)
<b>With Gutter Brush</b> . . . . .	76 in. (1930 mm)	88 in. (2235 mm)	88 in. (2235 mm)	100 in. (2540 mm)	100 in. (2540 mm)
<b>Working Width</b> . . . . .	75 in. (1905 mm)	86 in. (2184 mm)	86.1 in. (2187 mm)	98 in. (2489 mm)	98.1 in. (2492 mm)
<b>Height</b> . . . . .	29 in. (736 mm)	29 in. (736 mm)	29 in. (736 mm)	29 in. (736 mm)	29 in. (736 mm)
<b>Length</b> . . . . .	54 in. (1372 mm)	61 in. (1549 mm)	53.3 in. (1354 mm)	61 in. (1549 mm)	53.3 in. (1354 mm)
<b>Operating Weight</b>					
<b>Without Gutter Brush</b> . . . . .	750 lb. (340 kg)	1,500 lb. (681 kg)	950 lb. (431 kg)	1,700 lb. (772 kg)	1,050 lb. (476 kg)
<b>Hydraulic Flow:</b>					
<b>Minimum</b> . . . . .	12 gpm (45 L/min.)	10 gpm (37.8 L/min.)	10 gpm (37.8 L/min.)	10 gpm (37.8 L/min.)	10 gpm (37.8 L/min.)
<b>Maximum</b> . . . . .	22 gpm (83 L/min.)	30 gpm (113.5 L/min.)	30 gpm (113.5 L/min.)	30 gpm (113.5 L/min.)	30 gpm (113.5 L/min.)
<b>Hopper Capacity</b> . . . . .	13.2 cu. ft. (0.37 m <sup>3</sup> )	14.3 cu. ft. (0.40 m <sup>3</sup> )	15.75 cu. ft. (0.45 m <sup>3</sup> )	16.7 cu. ft. (0.47 m <sup>3</sup> )	18.21 cu. ft. (0.52 m <sup>3</sup> )
<b>Hopper Dumping</b> . . . . .	with skid steer bucket cylinders	with skid steer bucket cylinders	with skid steer bucket cylinders	with skid steer bucket cylinders	with skid steer bucket cylinders
<b>Vehicle Compatibility</b> . . . . .	313 and 315	317, 320, 325, 328, 332, CT322, and CT332	317, 320, 325, 328, 332, CT322, CT332, and 110TLB	317, 320, 325, 328, 332, CT322, and CT332	317, 320, 325, 328, 332, CT322, CT332, and 244J
<b>Options</b> . . . . .	gutter brush	gutter brush	gutter brush	gutter brush	gutter brush
<b>John Deere Standard Warranty</b> . . . . .	1-year unlimited hours	1-year unlimited hours	1-year unlimited hours	1-year unlimited hours	1-year unlimited hours

www.JohnDeere.com

## WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

