

## 332 Skid Steer

## Specs

<b>MANUFACTURER</b>	<b>John Deere</b>
<b>MODEL</b>	<b>332 Skid Steer</b>
<b>DATE OF SPECIFICATION</b>	Nov-05
<b>ENGINE</b>	
Manufacturer	John Deere
Model	5030Hw
Gross Horsepower (kw)	91 (68)
Net Horsepower (kw)	85 (63)
Rated RPM	2800
Grosspeak Torque, lb-ft (nm)	251 (340)
#Cylinders	5
Displacement, cuin(L)	186 (3.1)
Engine aspiration	Air-to-air aftercooled
Fuel Capacity, gal (L)	24 (91)
<b>HYDRAULIC SYSTEM</b>	
Standard Pump Flow, gpm (L/min.)	24 (91)
Optional High Flow, gpm (L/min.)	41 (155)
System Pressure, PSI (KPA)	3100 (21360)
Auxiliary Hydraulic Circuit, Std; Opt	Std
Hydraulic power, calculated, hp (kw)	43.4 (32.3)
Opt High-Flw Hyd pwr,calculated,hp(kw)	74.1 (55.6)
<b>PERFORMANCE</b>	
SAE Rated Oper Cap (ROC), lb (kg)	3,175 (1440)
SAE ROC with opt Counterweight, lb (kg)	3,525 (1599)
Tipping Load, standard, lb (kg)	6,350 (2880)
Boom, lb(kn)	6,650 (29.4)
Bucket, lb(kn)	11,600 (51.4)
Heaped Bucket Capacity, cu ft (cum)	17.66 (0.50)
Reference Bucket Width, in (mm)	78" (1980)
Self leveling bucket, Opt	Opt
<b>DRIVE TRAIN</b>	
Maximum Grnd Speed,stand,mph (kph)	7 (11.3)
Two Speed Trans Grnd Speed,mph(kph)	11.2 (18.0)
Drive chain size	100 Hz
Axle torque, lb-ft (nm)	6,930 (9396)
Standard Tire Size	14x17.5
<b>DIMENSIONS</b>	
Length with Bucket, in (mm)	138.5" (3520)
Length Without Bucket,in (mm)	115.5" (2930)
Width Without Bucket, in (mm)	77.1" (1960)
Height to ROPS, in (mm)	82.9" (2110)
Height to Hinge Pin, in (mm)	127" (127)
Dump Height, in (mm)	102" (2590)
Dump Reach, in (mm)	32" (810)
Dump Angle, degrees	45°

Bucket Rollback @ ground, degrees	35°
Wheelbase, in (mm)	48.6" (1230)
Ground Clearance, in (mm)	9.5" (241)
Angle of Departure, degrees	27°
<b>OPERATING WEIGHT, STANDARD LB (kg)</b>	<b>9,160 (4155)</b>

Specifications are based on published information at the time of publication. Specifications are subject to change without notice.