



JOHN DEERE



# TRENCHERS

TR36B | TR48B | TR60B



**WORKSITE PRO™**

COMMERCIAL WORKSITE PRODUCTS

## SPECIFICATIONS

# TR36B / TR48B / TR60B

- Worksite Pro Trenchers are designed for reliable, cost-effective production with Worksite Pro warranty and parts and service support in mind.
- Manual side shift conveniently allows trenching close to structures.
- A built-in skid shoe and indicators assist the operator in maintaining digging control.
- Axle design and rugged wheel motor offer extreme durability.
- Trenchers are built for easy maintenance with maintenance-free, double-sealed nose wheel bearings, and a heavy-duty planetary drive system that eliminates the need for unreliable chain reduction.
- Well-thought-out spring-loaded boom reduces shocks to the hydraulic motor, skid steer, and operator.
- Trencher design allows easy access into and out of skid steer.
- To further increase productivity, a standard heavy-duty crumbler allows removal of loose soil.
- Like all Worksite Pro attachments, these trenchers are optimized to work with John Deere 300-Series Skid Steers and CTLs, and are compatible with most competitive models. See your local John Deere skid steer dealer for details.

	TR36B	TR48B	TR60B
<b>Hydraulic Oil Flow</b> .....	16–44 gpm (60–167 L/min.)	16–44 gpm (60–167 L/min.)	27–44 gpm (102–167 L/min.)
<b>Maximum Continuous Operating Pressure</b> .....	3,300 psi (232 kg/cm <sup>3</sup> )	3,300 psi (232 kg/cm <sup>3</sup> )	3,300 psi (232 kg/cm <sup>3</sup> )
<b>Chain Type</b> .....	50,000 lb. (2270 kg) rated double standard anti-back flex	50,000 lb. (2270 kg) rated double standard anti-back flex	50,000 lb. (2270 kg) rated double standard anti-back flex
<b>Chain Pitch</b> .....	2 in. (51 mm)	2 in. (51 mm)	2 in. (51 mm)
<b>Boom Size</b> .....	36 in. (914 mm)	48 in. (1220 mm)	60 in. (1524 mm)
<b>Trench Width (standard)</b> .....	6 in. (152 mm)	6 in. (152 mm)	6 in. (152 mm)
<b>Spoil Auger Diameter (standard)</b> .....	14 in. (355 mm)	14 in. (355 mm)	14 in. (355 mm)
<b>Weight</b> .....	1,130 lb. (516 kg)	1,180 lb. (535 kg)	1,335 lb. (606 kg)
<b>Vehicle Compatibility</b> .....	317, 320, 325, 328, 332, CT322, CT332	317, 320, 325, 328, 332, CT322, CT332	325, 328, 332, CT332
<b>Overall Length</b> .....	73 in. (1854 mm)	86 in. (2184 mm)	99 in. (2515 mm)

**WORKSITE PRO™**



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

