



VIBRATORY ROLLERS

VR66C | VR73C | VR84C



WORKSITE PRO™

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

VR66C / VR73C / VR84C

- Worksite Pro™ vibratory rollers turn a skid steer into a powerful compactor, ideal for asphalt patch, foundation, trench, and flatwork compaction. They're very economical, since owning one eliminates the costs and maintenance of a self-propelled roller.
- Powered by standard hydraulics, rollers produce compaction forces up to 9,370 pounds.
- These attachments are easy to maneuver, with drum oscillation of ±15 degrees.
- Quik-Tatch™ compatible, they take only one minute to hook up.
- Drum and shaft bearings are lubricated and cooled in oil bath for long life.
- Bidirectional operation increases productivity.
- Like all Worksite Pro attachments, these vibratory rollers are optimized to work with John Deere 300-Series Skid Steers and Compact Track Loaders, and are compatible with most competitive models. Plus, they're backed by a one-year warranty and one-of-a-kind parts and service. See your local John Deere CWP dealer for details.

VR66C

VR73C

VR84C

Compatibility:

Smooth drum	317, 320, 325, 328, 332, CT322, and CT332	325, 328, 332, CT322, and CT332	325, 328, 332, CT322, and CT332
Sheep's-foot drum	317, 320, 325, 328, 332, CT322, and CT332	325, 328, 332, CT322, and CT332	N/A

Overall width 72 in. (1.8 m) 79 in. (2.0 m) 90 in. (2.3 m)

Overall length 39 in. (99 cm) 39 in. (99 cm) 39 in. (99 cm)

Overall height 31 in. (79 cm) 31 in. (79 cm) 31 in. (79 cm)

Drum width 66 in. (1.7 m) 73 in. (1.8 m) 84 in. (2.1 m)

Drum diameter:

Smooth	24 in. (61.0 cm)	24 in. (61.0 cm)	24 in. (61.0 cm)
Sheep's-foot (without pads)	20 in. (51.0 cm)	20 in. (51.0 cm)	N/A

Drum oscillation ±15 deg. ±15 deg. ±15 deg.

Dynamic force 7,800 lbf (3538 kg) 8,550 lbf (3878 kg) 9,370 lbf (4250 kg)

Vibrations per minute:

Range	11–25 gpm (41–95 L/min.)	11–25 gpm (41–95 L/min.)	11–25 gpm (41–95 L/min.)
Optimum performance	20 gpm (75.7 L/min.)	20 gpm (75.7 L/min.)	20 gpm (75.7 L/min.)

Operating weight:

Smooth drum	2,150 lb. (975 kg)	2,300 lb. (1043 kg)	2,530 lb. (1148 kg)
Sheep's-foot drum	2,085 lb. (945 kg)	2,230 lb. (1012 kg)	N/A

www.JohnDeere.com

WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

